

ECA Bond Breaker Tape

POLYETHYLENE TAPE

DESCRIPTION

ECA Bond Breaker Tape is a polyethylene tape used to prevent three-way adhesion of sealant and ensure the correct and uniform sealant depth along the whole length of a joint. It serves as a barrier that fills gaps in shallow joints where ECA Backing Rod cannot be used.

USES

- Used to fill gaps in joints where ECA Backing Rod cannot be applied due to shallow depth
- Provides a suitable substrate for effective sealing in shallow joints
- Prevents three-way adhesion of sealant, ensuring proper bonding to desired surfaces
- Helps achieve consistent and uniform sealant depth along the joint length
- Enhances appearance and longevity of sealant applications, contributing to overall project quality in construction or glazing

ADVANTAGES

- Quick and easy to apply
- Reduces sealant usage
- Improves sealant performance by obtaining easily the correct joint dimensions
- Flexible – won't bubble or blister
- Stops 3 way adhesion of a sealant eliminating movement cracks

PACKAGING

ECA Bond Breaker Tape is supplied in the following sizes (width x length x thickness):

- 50 mm x 3.5 m x 5 mm
- 40 mm x 3.5 m x 5 mm

STORAGE

ECA Bond Breaker Tape should be stored in a dry area.

HEALTH AND SAFETY

For more information, please check the Material Safety Data Sheet.

CONTACT

Al-Faiha for Engineering Products is the exclusive licensee manufacturer for ECA.

For more information, please contact us at techsupport@alfaihaengineering.com.

DISCLAIMER

ECA aims to ensure the accuracy of information and recommendations in the product literature. However, due to variations in materials, substrates, and site conditions, and without control over product application, storage, weather, and usage conditions, ECA cannot be held liable for any resulting issues.