

POLYSULPHIDE SEALANT PRIMER

PRIMER USED WITH EUNISEAL VERTISEAL AND EUNISEAL PARASEAL

DESCRIPTION

POLYSULPHIDE SEALANT PRIMER is a single component adhesion promoting liquid primer designed for the preparation of joint surfaces before the application of EUNISEAL VERTISEAL and EUNISEAL PARASEAL when applied to porous substrates. This primer plays a crucial role in enhancing the adhesion and performance of the subsequent sealant application by ensuring proper surface preparation. The liquid formulation is tailored to optimize the bonding properties of the sealants, contributing to the overall effectiveness of the sealing process.

single component adhesion

USES

POLYSULPHIDE SEALANT PRIMER is employed in the preparation of joints in porous substrates, such as concrete, blocks, brickwork, stonework, asbestos, and timber.

ADVANTAGES

- Easily applied, quick drying.
- No thinning required.
- Single component low viscosity easy to apply.
- Strengthens the adhesion of joint sealants to porous surfaces.

APPLICATION

Surface Preparation

Before applying POLYSULPHIDE SEALANT PRIMER, meticulous surface preparation is essential. Ensure that all surfaces are thoroughly cleaned, completely dry, and free from any dust, dirt, paint, loose materials, oil, grease, sealers, curing compounds, waxes, or other contaminants.

Application Instructions

To apply POLYSULPHIDE SEALANT PRIMER, pour a small amount into a clean container, ensuring the main container is tightly resealed to preserve its properties. Masking tape shall be applied on both the edges of the groove before applying the primer and shall be removed, once the sealant installation is complete.

Use a soft brush to liberally apply a coat of primer to the desired surface. Allow the primer to become tack-free before proceeding with the installation of sealants such as EUNISEAL VERTISEAL and EUNISEAL PARASEAL. It is important to note that if the primer is left for more than 3 hours, re-priming becomes necessary. Additionally, be aware that the primers are solvent-based, necessitating proper handling and ventilation during application.

COVERAGE

1 liter covers approx. 150 linear meters for 100mm deep joint.

PACKAGING

POLYSULPHIDE SEALANT PRIMER is supplied in 1 Liter cans.

STORAGE

POLYSULPHIDE SEALANT PRIMER should be stored and maintained under cover, away from direct sunlight, and ensure protection from extremes of temperature. In tropical climates, it is imperative to store the product in an air-conditioned environment to maintain its stability and effectiveness. Shelf life is 12 months from date of manufacture.

HEALTH AND SAFETY

For more information, please check the Material Safety Data Sheet.

CONTACT

Al-Faiha for Engineering Products is the exclusive licensee manufacturer for ECA.

For more information, please contact us at techsupport@alfaihaengineering.com.

DISCLAIMER

ECA aims to ensure the accuracy of information and recommendations in the product literature. However, due to variations in materials, substrates, and site conditions, and without control over product application, storage, weather, and usage conditions, ECA cannot be held liable for any resulting issues.

21-01-2024